

88
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 11 \\ S 14 \\ 1921 \end{array}$$

from which,

A fir, 22 ins. diam., bears N.11*W., 34 lks. dist.,
mkd. $\frac{1}{4}$ S 11 B T

A pine, 36 ins. diam., bears S.4*W., 48 lks. dist.,
mkd. $\frac{1}{4}$ S 14 B T

Descend 220 ft. on NW. slope.

- 50.50 Draw, course NE.; asc. 50 ft. on NE. slope.
55.40 Spur, slopes N.; desc. 135 ft. on NW. slope.
61.55 Foot of descent, on bench, bears NE. and SW.
65.55 Leave bench, bears NE. and SW.; desc. 265 ft. on NW. slope, to

80.36 The cor. of secs. 10, 11, 14, and 15.

Land; mountainous.

Soil; clay loam, stony in places, 2nd and 3rd rate.

Timber; fir, hemlock, cedar, and pine.

Undergrowth; chinquapin, fir, hazel.

N.0*02*W., bet. secs. 10 and 11.

Over mountainous land, through heavy timber and dense undergrowth.

Desc. 220 ft. on N. slope.

17.10 Left bank of South Umpqua River, 100 lks. wide, course SW.

18.75 Right bank of river; asc. 15 ft. on SE. slope, to

21.40 Trail, Tiller to Grasshopper Ranger Station, bears NE. and SW.; thence over nearly level land.

33.80 Begin ascent, 50 ft. on SE. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked