

County Surveyor's Record, ⁹²Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

From the cor. of secs. 21, 22, 27 and 28, heretofore described

N, 0° 02' W., bet. secs. 21 and 22.

Over mountainous land, through heavy timber and scattering undergrowth.

Desc. 30 ft. on NW. slope, to

1.00 Creek, 15 lks. wide, course NE.; desc. 10 ft. along W. side of creek.


4.25 Bend of same creek, bears SE., course NE.; asc. 25 ft. on SE. slope.

6.25 Bench, bears NE. and SW.; desc. 50 ft. on rolling E. slope.

22.65 Ravine, course NE.; asc. 140 ft. on SE. slope.

36.90 Low spur, slopes NE.; desc. 15 ft. on N. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked



from which,

A fir, 9 ins. diam., bears N. 7° E., 8 lks. dist., mkd. 1/4 S 22 B T


A fir, 18 ins. diam., bears S. 74° W., 24 lks. dist., mkd. 1/4 S 21 B T

Gradually descend 50 ft. on N. slope, to

60.00 Flat spur, slopes NE.; desc. 400 ft. on N. slope.

78.15 Buckeye Creek, 25 lks. wide, course NW.; thence over creek bottom.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap marked



from which,