

Subdivisions of T. 29 S., R. 1 E.

CHAINS

A fir, 16 ins. diam., bears N.14*E., 67 lks. dist.,
mkd. T 29 S R 1 E S 15 B T

A fir, 10 ins. diam., bears S.38*E., 17 lks. dist.,
mkd. T 29 S R 1 E S 22 B T

A fir, 16 ins. diam., bears S.43*W., 65 lks. dist.,
mkd. T 29 S R 1 E S 21 B T

A fir, 14 ins. diam., bears N.67*W., 37 lks. dist.,
mkd. T 29 S R 1 E S 16 B T

Land; mountanous and rolling.

Soil; clay loam, 2nd rate.

Timber; fir, cedar, and pine.

Undergrowth; chinquapin, fir, hazel.

40.00 N.89*58'E., on a random line, bet. secs. 15 and 22.
Set temp. $\frac{1}{4}$ sec. cor.

80.16 Intersect N. and S. line, 19 lks. N. of the cor. of
secs. 14, 15, 22, and 23, heretofore described.

Thence

N.89*54'W., on a true line, bet. secs. 15 and 22.

Over mountainous land, through heavy timber and dense
undergrowth.

Across bench.

2.50 Leave bench, bears NE. and SW.; desc. 335 ft. on NW.
slope.

20.00 Foot of descent, on bench, bears NE. and SW.

26.00 Leave bench, bears NW. and SE.; asc. 75 ft. on NE.
slope.

32.00 Rocky Point, slopes N.; descend 110 ft. on NW. slope.

36.15 Buckeye Creek, 25 lks. wide, course SW.; thence over
creek bottom.

40.08 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S\ 15}{S\ 22}$
1921