

County Surveyor's Record, <sup>74</sup>Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

from which,

A yew, 14 ins. diam., bears N.34\*W., 32 lks.

dist., mkd. 1/4 S 15 B T

A hemlock, 7 ins. diam., bears S.11\*E., 18 lks.

dist., mkd. 1/4 S 22 B T

Asc. 140 ft. on SE. slope.

54.35 Rocky spur, slopes S.; desc. 180 ft. on SW. slope, to

80.16 The cor. of secs. 15, 16, 21, and 22.

Land; mountainous.

Soil; stony clay loam, 2nd and 3rd rate.

Timber; fir, hemlock, cedar, and pine.

Undergrowth; chinquapin, vine maple, hazel, hemlock.

N.0\*02\*W., bet. secs. 15 and 16.

Over mountainous land, through heavy timber and dense undergrowth.

Over creek bottom.


3.00 Leave creek bottom, bears NW. and SE.; asc. 35 ft. on SW. slope.

6.00 Spur, slopes W.; desc. 25 ft. on NW. slope.

12.00 Foot of descent, on bench, bears NE. and SW.

22.00 Leave bench, bears NW. and SE.; asc. 165 ft. on SW. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked,



from which,

A fir, 14 ins. diam., bears N.18\*E., 39 lks.

dist., mkd. 1/4 S 15 B T

A fir, 20 ins. diam., bears N.35\*W., 87 lks.

dist., mkd. 1/4 S 16 B T

Asc. 110 ft. on SW. slope.