

98
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

57.60 Creek, 2 lks. wide, course SE.; asc. 115 ft. on SW. slope.

68.35 Same creek, course SW.; asc. 200 ft. on SE. slope; to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T29S	R1E
S4	S3
S9	S10
1921	

from which,

A fir, 18 ins. diam., bears N.42°E., 25 lks. dist.,
mkd. T 29 S R 1 E S 3 B T

A fir, 12 ins. diam., bears S.81°E., 45 lks. dist.,
mkd. T 29 S R 1 E S 10 B T

A fir, 24 ins. diam., bears S.21°W., 20 lks. dist.,
mkd. T 29 S R 1 E S 9 B T

A fir, 14 ins. diam., bears N.69°W., 30 lks. dist.,
mkd. T 29 S R 1 E S 4 B T

Land; mountainous.

Soil; stony clay loam, 2nd and 3rd rate.

Timber; fir, cedar, hemlock, and pine.

Undergrowth; chinquapin, fir, vine maple, hazel.

S.89°52'E., on a random line, bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.,

79.86 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 2, 3, 10 and 11, heretofore described.

Thence

N.89°47'W., on a true line, bet. secs. 3 and 10.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 185 ft. on E. slope.

15.70 Spur, slopes S.; desc. 15 ft. on SW. slope.