

Subdivisions of T. 29 S., R. 1 E.

CHAINS


50.50 Top of bluff; descend 110 ft. on bluff.  
 51.60 Foot of bluff; descend 135 ft. on W. slope.  
 56.00 Draw, course N.; asc. 190 ft. on NE. slope, to  
 80.14 The cor. of secs. 16, 17, 20 and 21.  
 Land; mountainous.  
 Soil; clay loam and rock, 2nd, 3rd, and 4th rate.  
 Timber; fir, cedar, pine and hemlock.  
 Undergrowth; chinquapin, fir, hazel.

N.0\*03'W., bet. secs. 16 and 17.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 200 ft. on N. slope.

9.10 Ravine, course NE.; asc. 55 ft. on SE. slope.  
 16.00 Ridge, bears NE. and SW.; descend 175 ft. on NW. slope,  
 to  
 29.00 Top of bluffs; descend 340 ft. on bluffs.  
 34.90 Foot of bluffs; desc. 155 ft. on NW. slope.  
 38.65 Left bank of south Umpqua river, 100 lks. wide, course SW.  
 40.00 True point for  $\frac{1}{4}$  sec. cor., in river.  
 40.20 Right bank of river; asc. 10 ft. on SE. slope.  
 40.50 Top of river bank; thence along edge of bank.  
 41.50 Leave river bank, bears NE.; thence over bench.  
 42.19 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
 the ground, for witness cor. to the  $\frac{1}{4}$  sec. cor.,  
 with brass cap marked



from which

A fir, 8 ins. diam., bears S.42\*E., 18 lks. dist.,

mkd. W C  $\frac{1}{4}$  S 16 B T

A hemlock, 10 ins. diam., bears N.49\*W., 49 lks. dist.,

mkd. W C  $\frac{1}{4}$  S 17 B T