

County Surveyor's Record, ¹⁰⁴Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

43.25 Trail, Tiller to Grasshopper Ranger Station, bears NE. and SW.; leave bench, bears NE. and SW.; asc. 770 ft. on S. slope.

74.60 Ridge, divide bet. South Umpqua River and Rock Creek, bears NE. and SW.; desc. 190 ft. on NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap marked

T29S	R1E
S8	S9
S17	S16
1921	

from which,

A hemlock, 10 ins. diam., bears N.11*E., 13 lks.

dist., mkd. T 29 S R 1 E S 9 B T

A fir, 8 ins. diam., bears S.24*E., 31 lks.

dist., mkd. T 29 S R 1 E S 16 B T

A fir, 6 ins. diam., bears S.56*W., 29 lks.

dist., mkd. T 29 S R 1 E S 17 B T

A hemlock, 12 ins. diam., bears N.11*W., 14 lks.

dist., mkd. T 29 S R 1 E S 8 B T

Cor. No. 12, H. E. S. No. 144, which is a porphyry stone, 10x22x12 ins. above ground, firmly set, marked and witnessed as described in field notes of H. E. S. No. 144, bears N.84*17'W., 12.44 chs. dist.

Land; mountainous.

Soil; stony, clay loam, 2nd and 3rd rate.

Timber; fir, hemlock, cedar and pine.

Undergrowth; chinquapin, fir, hazel, hemlock.

N.89*54'E., on a random line, bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 9, 10, 15 and 16, heretofore described.

Thence