

Subdivisions of T. 29 S., R. 1 E.

CHAINS

- 8.30 Foot of descent; enter flat, and dense thicket, bears NE. and SW.
- 9.30 Rock Creek, 10 lks. wide, course SW.
- 11.80 Rock Creek, 10 lks. wide, course SE.
- 14.00 Rock Creek, 10 lks. wide, course SW.
- 34.30 Leave dense thicket, bears NE. and SW.
- 34.45 Trail, Tiller to Quartz Mountain Ranger Station, bears NE. and SW.; asc. 40 ft. on SE. slope, to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S 8 S 9} \\ 1921 \end{array}$$

from which

A fir, 10 ins. diam., bears S.41*E., 26 lks. dist.,
mkd. $\frac{1}{4}$ S 9 B T

A fir, 48 ins. diam., bears S.81*W., 7 lks. dist.,
mkd. $\frac{1}{4}$ S 8 B T

Cor. No. 30, H. E. S. No. 143, which is a porphyry stone, 10x16x12 ins. above ground, firmly set, marked and witnessed as described in field notes of H. E. S. No. 143, bears N.10*26'E., 13.98 chs. dist.

Asc. 65 ft. on SE. slope.

- 50.35 Low spur, slopes E.; desc. 80 ft. on N. slope.
- 55.95 Creek, 2 lks. wide, course SE.; thence over creek bottom.
- 60.10 Leave creek bottom, bears E. and W.; asc. 265 ft. on S. slope.
- 72.00 Top of ascent; thence over E. slope.
- 76.00 Begin ascent; 20 ft. on SE. slope.
- 79.35 Spur, slopes SE.; desc. 10 ft. on NE. slope, to
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked