

## Subdivisions of T. 29 S., R. 1 E.

## CHAINS

- 4.65 Creek, 5 lks. wide, course NE.; asc. 200 ft. on SE. slope.
- 31.00 Top of ascent; thence over E. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 19 \text{ S } 20 \\ | \\ 1921 \end{array}$$

from which

A fir, 8 ins. diam., bears N.34\*E., 57 lks. dist.,  
mkd.  $\frac{1}{4}$  S 20 B T

A fir, 30 ins. diam., bears S.88\*W., 25 lks. dist.,  
mkd.  $\frac{1}{4}$  S 19 B T

Desc. 370 ft. on NE. slope.

- 59.75 Creek, 2 lks. wide, course NE.; thence over E. slope.
- 63.80 Creek, 2 lks. wide, course NE.
- 68.10 Small spur, slopes NE.; desc. 100 ft. on NE. slope.
- 75.00 Ravine, course NE.; asc. 50 ft. on SE. slope, to
- 80.00 Point for cor. of secs. 17, 18, 19, and 20, falls on sloping bedrock; impracticable to set iron post, and no stones available for mound; therefore, at exact corner point,

Cut a cross (x) with 5 grooves E., and 3 grooves S. of cross, for cor. of secs. 17, 18, 19 and 20; from which

A fir, 12 ins. diam., bears N.67\*E., 35 lks. dist.,  
mkd. T 29 S R 1 E S 17 B T

A fir, 10 ins. diam., bears S.55\*E., 40 lks. dist.,  
mkd. T 29 S R 1 E S 20 B T

A fir, 8 ins. diam., bears S.21\*W., 75 lks. dist.,  
mkd. T 29 S R 1 E S 19 B T

A white oak, 5 ins. diam., bears N.33\*W., 60 lks. dist.,  
mkd. T 29 S R 1 E S 18 B T