

114  
County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 1 E.

CHAINS

53.70 Creek, 4 lks. wide, course SE.; asc. 625 ft. on S. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap marked

T29S	R1E
S7	S8
S18	S17
1921	

From which

A fir, 12 ins. diam., bears N.42\*E., 19 lks. dist.,  
mkd. T 29 S R 1 E S 8 B T

A fir, 40 ins. diam., bears S.23\*E., 62 lks. dist.,  
mkd. T 29 S R 1 E S 17 B T

A fir, 24 ins. diam., bears S.83\*W., 47 lks. dist.,  
mkd. T 29 S R 1 E S 18 B T

A dogwood, 6 ins. diam., bears N.55\*W., 37 lks. dist.,  
mkd. T 29 S R 1 E S 7 B T

Land; mountainous.

Soil; stony clay loam, 2nd and 3rd rate.

Timber; fir, hemlock, cedar, and pine.

Undergrowth; chinquapin, hazel, fir, vine maple.

S.89\*50'E., on a random line, bet. secs. 8 and 17.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.08 Intersect N. and S. line, 23 lks. S. of the cor. of secs.  
8, 9, 16 and 17, heretofore described.

Thence

West, on a true line, bet. secs. 8 and 17.

Over mountainous land, through heavy timber and dense  
undergrowth.

Asc. 25 ft. on NE. slope.

2.25 Spur, slopes N.; desc. 95 ft. on NW. slope.