

Subdivisions of T. 29 S., R. 1 E.

CHAINS

67.50 Spur, slopes SE.; desc. 300 ft. on NE. slope, to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
 the ground, for cor. of secs. 5, 6, 7, and 8, with
 brass cap marked

T29S	R1E
S6	S5
S7	S8
1921	

from which

A fir, 12 ins. diam., bears N.53*E., 42 lks. dist.,
 mkd. T 29 S R 1 E S 5 B T

A hemlock, 7 ins. diam., bears S.55*E., 3 lks. dist.,
 mkd. T 29 S R 1 E S 8 B T

A yew, 14 ins. diam., bears S.2*W., 21 lks. dist.,
 mkd. T 29 S R 1 E S 7 B T

A hemlock, 24 ins. diam., bears N.82*W., 66 lks. dist.,
 mkd. T 29 S R 1 E S 6 B T

Land; mountainous.

Soil; clay loam, stony in places, 2nd and 3rd rate.

Timber; fir, pine, hemlock, and cedar.

Undergrowth: chinquapin, hemlock, fir, hazel, vine maple.

East, on a random line, bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect N. and S. line, 14 lks. S. of the cor. of
 secs. 4, 5, 8 and 9, heretofore described.

Thence

S.89*54'W., on a true line, bet. secs. 5 and 8.

Over mountainous land, through heavy timber and dense
 undergrowth.

Asc. 365 ft. on NE. slope.

20.75 Ridge, bears NW. and SE.; desc. 370 ft. on SW. slope,
 to