

Dependent Resurvey of S. bdy. of T. 29 S., R. 1 E.

CHAINS

Resurvey

Note: For topography of this line see field notes of the resurvey of this line by Fred Mensch, U. S. D. S., under contract No. 797, dated April 19, 1910.

The cor. set. for secs. 3, 4, 33 and 34, is a cross (X) on bed-rock, witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 33 and 34 only.

I mark the rock S 34 on NE., and S 33 on NW. side of the cross and obliterate the marks on the bearing trees for secs. 3 and 4.

Thence

West, resurveying the S. bdy. of sec. 33.

38.59 Point for the $\frac{1}{4}$ sec. cor. of sec. 4 only.

Set a conglomerate stone 20x12x8 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 4 only, marked $\frac{1}{4}$ S 4 on S. face; from which

A fir, 20 ins. diam., bears S.38*E., 37 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T

A fir, 9 ins. diam., bears S.80*W., 33 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T

No iron post available for this corner.

40.06 The $\frac{1}{4}$ sec. cor. est. for secs. 4 and 33, which is a conglomerate stone 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

Hereafter this cor. will refer to sec. 33 only.

I mark the cor. stone $\frac{1}{4}$ S 33 on N. face; from which

A fir, 6 ins. diam., bears N.23*E., 18 lks. dist.,
mkd. $\frac{1}{4}$ S 33 B T., old B T

A pine, 44 ins. diam., bears N.57*W., 48 lks. dist.,
mkd. $\frac{1}{4}$ S 33 B T., new B T.

I obliterate the marks on the old B T in sec. 4.