

County Surveyor's Record, <sup>26</sup>Douglas County, Oregon

Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.

## CHAINS

- 78.62 Point of intersection of line bet. secs. 4 and 5, T. 30 S., R. 1 E., determined as hereinafter set forth. Set a conglomerate stone, 20x14x4 ins., 15 ins. in the ground, for closing cor. of secs. 4 and 5, marked with
- 4 grooves on E.,  
CC and 6 grooves on S., and  
2 grooves on W. face; from which
- A madrona, 18 ins. diam., bears S.21\*E., 22 lks.  
dist., mkd. T 30 S R 1 E S 4 C C B T
- A fir, 10 ins. diam., bears S.47\*W., 25 lks.  
dist., mkd. T 30 S R 1 E S 5 C C B T
- No iron post available for this cor.
- 80.00 The cor. established for secs. 4, 5, 32 and 33, which is a conglomerate stone, 12x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.
- Hereafter this cor. will refer to secs. 32 and 33 only. I mark the stone S 33 on the NE., and S 32 on NW. face and obliterate the marks on the old bearing trees S. of the line.
- 
- West, resurveying S. bdy. of sec. 32, T. 29 S., R. 1 E.
- 38.84 Point for the  $\frac{1}{4}$  sec. cor. of sec. 5 only. Set a conglomerate stone, 20x10x6 ins. 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., of sec. 5 only, marked  $\frac{1}{4}$  S 5 on S. face; from which
- A fir, 12 ins. diam., bears S.38\*E., 59 lks.  
dist., mkd.  $\frac{1}{4}$  S 5 B T
- A fir, 30 ins. diam., bears S.12\*W., 27 lks.  
dist., mkd.  $\frac{1}{4}$  S 5 B T
- No iron post available for this cor.
- 40.14 The  $\frac{1}{4}$  sec. cor. established for secs. 5 and 32, which is