

Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.

CHAINS

A fir, 20 ins. diam., marked $\frac{1}{4}$ S 32 on N., and S 5 on S. side.

Hereafter this cor. will refer to sec. 32 only.

I obliterate the marks on the S. side of the cor. tree, from which

A fir, 6 ins. diam., bears N.40*E., 9 lks. dist.,
mkd. $\frac{1}{4}$ S 32 B T., new B T.

A fir, 20 ins. diam., bears N.33*W., 4 lks. dist.,
mkd. $\frac{1}{4}$ S 32 B T., old B T

I obliterate the marks on the old B T in sec. 5.

79.06 Point of intersection of line bet., secs. 5 and 6, T. 30 S., R. 1 E., determined as hereinafter set forth. Set a conglomerate stone, 20x16x7 ins. 15 ins. in the ground, for closing cor. of secs. 5 and 6, marked with

5 grooves on E.,

CC and 6 grooves on S., and

1 groove on W. face; from which

A fir, 16 ins. diam., bears S.18*E., 33 lks. dist.,
mkd. T 30 S R 1 E S 5 CC B T

A fir, 14 ins. diam., bears S.18*W., 27 lks. dist.,
mkd. T 30 S R 1 E S 6 C C B T

No iron post available for this corner.

80.04 The cor. established for secs. 5, 6, 31 and 32, which is a basalt stone, 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 31 and 32 only.

I mark the cor. stone, S 32 on NE., and S 31 on NW.

face, and obliterate the marks on old bearing trees S. of line.