

128  
County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.

## CHAINS

West, resurveying the S. bdy. of sec. 31, T 29 S., R.  
1 E.,

39.02 Point for the  $\frac{1}{4}$  sec. cor. of sec. 6 only.

Set a conglomerate stone, 20x12x5 ins., 15 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., of sec. 6 only, marked  
 $\frac{1}{4}$  S 6 on S; face; from which,

A fir, 18 ins. diam., bears S.57\*E., 50 lks.  
dist., mkd.  $\frac{1}{4}$  S 6 B T

A fir, 18 ins. diam., bears S.73\*W., 26 lks.  
dist., mkd.  $\frac{1}{4}$  S 6 B T

No iron post available for this cor.

40.15 The  $\frac{1}{4}$  sec. cor. established for secs. 6 and 31., which  
is a conglomerate stone, 10x8x5 ins. above ground,  
firmly set, marked and witnessed as described by the  
surveyor general.

Hereafter this cor. will refer to sec. 31 only.

I mark the cor. stone  $\frac{1}{4}$  S 31 on N. face; from which;

A hemlock, 8 ins. diam., bears N.1\*E., 11 lks.  
dist., mkd.  $\frac{1}{4}$  S 31 B T., old B T.

A cedar, 10 ins. diam., bears N.78\*W., 38 lks.  
dist., mkd. ;  $\frac{1}{4}$  S 31 B T.

I obliterate the marks on the old B T in sec. 6.

79.36 The cor. of Tps. 29 and 30 S., R. 1 E., on the  
Willamette Meridian, hereinbefore described.