

County Surveyor's Record, Douglas County, Oregon

East, South, and North Boundaries and Subdivisions of T. 29 S., R. 2 E., as surveyed by Fred Mensch, U. S. Cadastral Engineer, and Lincoln E. Wilkes, U. S. Cadastral Engineer, under Special Instructions, dated Dec. 21, 1920.

CHAINS

South Boundary of T. 29 S., R. 2 E.

From the SE. corner of township,  
West, on a true line, bet. secs. 1 and 36.  
Over mountainous land, through heavy timber and dense undergrowth.  
Ascend gradually.

- 10.40 Spur, slopes NW. Descend 400 ft. to  $\frac{1}{4}$  sec. cor.
- 27.80 Brook, 1 link wide, course NW.
- 39.64 Dry gulch, course NW.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$	S 36
—	S 1
	1923

from which

A fir, 18 ins. dia., bears N. 48\* W., 28 lks. dist., marked  $\frac{1}{4}$  S 36 BT.

A fir, 12 ins. dia., bears S. 22\* E., 32 lks. dist., marked  $\frac{1}{4}$  S 1 BT.

Descend 180 ft. over SW. slope to sec. cor.

- 52.83 Brook, 1 link wide, course south.
- 55.04 Brook, 1 link wide, course SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap marked

T 29 S	R 2 E
S 35	S 36
—	—
S 2	S 1
T 30 S	
1923	

from which

A madrona, 6 ins. dia., bears N. 66\* E., 10 lks. dist., marked T 29 S R 2 E S 36 BT.

A madrona, 7 ins. dia., bears S. 43\* E., 34 lks. dist., marked T 30 S R 2 E S 1 BT.

A madrona, 6 ins. dia., bears S. 29\* W., 6 lks. dist., marked T 30 S R 2 E S 2 BT.

A madrona, 12 ins. dia., bears N. 66\* W., 5 lks. dist., marked T 29 S R 2 E S 35 BT.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3 rd rate.