

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 2 E.

CHAINS

A Fir, 12 ins. diam., bears S.68*W., 29 lks. dist.

Marked T 30 S R 2 E S 4 B T.

A Fir, 14 ins. diam., bears N.5*W., 7 lks. dist.

Marked T 29 S R 2 E S 33 B T.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, Fir, Hemlock, Cedar and Pine.

Undergrowth, Rhododendron, Vine Maple and Hemlock.

West, on a true line, bet. Secs. 4 and 33.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 235 ft. over SE. slope.

11.10 Spur, slopes S. Descend 76 ft. to

15.60 Brook, 5 lks. wide, C. S. Ascend 225 ft. over SE. slope

19.40 A trail, bears NE. and SW.

33.40 Spur, slopes S. Descend 140 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 Sec. cor., with brass cap marked

S 33	
1/4 ———	
S 4	
1923	from which

A Fir, 13 ins. diam., bears N.7*E., 47 lks. dist.

Marked 1/4 S 33 B T.

A Fir, 6 ins. diam., bears S.47*W., 63 lks. dist.

Marked 1/4 S 4 B T.

Ascend 40 ft. to

43.00 Enter bench land, sloping S.

47.00 Leave bench, bearing NE. and SW. Descend 300 ft. over SW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 4, 5, 32 and 33, with brass cap marked

T 29 S	R 2 E	
S 32	S 33	
S 5	S 4	
T 30 S		from which
1923		