


County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 2 E.

CHAINS

77.50 Bank of same river, at bend, course NW., from NE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.



from which

- An alder, 8 ins. diam., bears N. 79*E., 15 lks. dist.,
mkd. T 29 S R 2 E S 32 B T
- An alder, 10 ins. diam., bears S. 44*E., 36 lks. dist.,
mkd. T 30 S R 2 E S 5 B T
- A fir, 24 ins. diam., bears S. 61*W., 58 lks. dist.,
mkd. T 30 S R 2 E S 6 B T
- An alder, 10 ins. diam., bears N. 16*W., 37 lks. dist.,
mkd. T 29 S R 2 E S 31 B T

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate. & 4th rate.

Timber, fir, pine and cedar.

Undergrowth, rhododendron, vinemaple and fir.

West, on a true line, bet. secs. 6 and 31.

Over mountainous land, through heavy timber and dense undergrowth.


Along S. side of S. Fork of S. Umpqua River.

6.15 Intersect left bank of said S. Fork of S. Umpqua River at bend, course NW. from NE.

17.80 Middle of same river, 120 lks. wide, course SW.
Ascend gradually along SE. slope.

37.00 Spur, slopes S. Descend 40 ft., over SW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, fo bed rock, (supported by a mound of stone, 3 ft. base, 1½ ft. high, around post) with brass cap marked



from which

An oak, 9 ins. diam., bears N. 42* W., 65 lks. dist.,
marked ¼ S 31 B T