


County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 29 S., R. 2 E.

CHAINS Descend 660 ft. over N. slope to creek.
 57.00 Leave burn, enter green timber, bearing NE. and SW.
 72.55 Creek, 10 lks. wide, course W. Ascend 100 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
 the ground, for cor. of Secs. 25, 30, 31 and 36, with
 brass cap marked



from which

A Cedar, 26 ins. diam., bears N.63*E., 89 lks.

Marked T 29 S R 3 E S 30 B T.

A Fir, 52 ins. diam., bears S.75*E., 50 lks.

Marked T 29 S R 3 E S 31 B T.

A Fir, 16 ins. diam., bears S.35*W., 56 lks.

Marked T 29 S R 2 E S 36 B T.

A Fir, 48 ins. diam., bears N.79*W., 71 lks.

Marked T 29 S R 2 E S 25 B T.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, Fir, Pine and Cedar.

Undergrowth, Rhododendron, Vine Maple, and young trees.

North, bet. Secs. 25 and 30.

Over mountainous land, through heavy timber and dense
 undergrowth.

Ascend 630 ft. over S. slope.

24.75 Spur, slopes SW. Descend 210 ft. over NW. slope.

34.85 Brook, 1 link wide, course W.

36.95 Brook, 1 link wide, course SW. Ascend gradually.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor., with brass cap marked



from which

A Fir, 20 ins. diam., bears S.62*E., 37 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.

A Fir, 40 ins. diam., bears N.71*W., 38 lks. dist.