

East Boundary of T. 29 S., R. 2 E.

CHAINS

ground, for 1/4 Sec. cor., with brass cap marked

1/4  
S 13 | S 18  
1923

from which

A Fir, 8 ins. diam., bears S.60\*E., 21 lks. dist.,  
Marked 1/4 S 18 B T.

A Fir, 6 ins. diam., bears S.66\*W., 18 lks. dist.,  
Marked 1/4 S 13 B T.

A rock pinnacle, or butte, about 100 ft. high, 100 ft.  
diam., bears N.35\*W., 4.25 chs. dist.

47.25 A bluff, 150 ft. high bears NE. and SW., facing SE.  
From a point on line at 45.27 chs. I run a traverse line  
N.18\*00'E., 4.75 chs.; thence  
N.45\*00'W., 1.22 chs.; Summit of spur, 170 ft. higher  
than 1/4 Sec. cor., bears NE.  
and SW.  
Grasshopper Lookout Station,  
bears N.45\*E.  
Descend steep NW. slope 150 ft. to  
3.56 chs.; Foot of bluff bears N.25\*E.,  
and SW.  
North, On offset line, over steep  
broken NW. slope.  
5.00 chs.; Offset.  
East, 1.05 chs.; To true line at 57.31 chs.

Course	Dist.	North	South	East	West
North	45.27	45.27			
N.18*0'E.	4.75	4.52		1.47	
N.45*0'W.	3.56	2.52			2.52
North,	5.00	5.00			
East,	1.05			1.05	
Totals		57.31	0.00	2.52	2.52

57.31 Continue on true line.  
80.00 A point 450 ft. lower than summit of spur;  
Set an iron post, 3 ft. long, 2 ins. diam.,  
27 ins. in the ground, for cor. of Secs.  
7, 12, 13 and 18, with brass cap marked

T 29 S  
R 2 E | R 3 E  
S 12 | S 7  
S 13 | S 18  
1926

from which

A White Fir, 16 ins. diam., bears N.70 1/2 \*E., 42 lks.  
dist., marked T 29 S R 3 E S 7 B T.

A Red Cedar, 10 ins. diam., bears S.42\*E., 27 lks.  
dist., marked T 29 S R 3 E S 18 B T.

