

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S. R. 2 E.

CHAINS

From the cor. of Secs. 1, 2, 35 and 36 on South Bdy. of Tp. already described,

N.0\*1'W., bet. Secs. 35 and 36.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 25 ft. to

4.00 Spur, slopes W.

6.14 Shallow draw, opens NW; ascend 80 ft. to

15.50 Spur, slopes W. Descend 310 ft. over NW. slope.

26.46 Brook, 1 lk. wide, C. NW. Ascend 100 ft. over SW. slope.

32.50 Spur, slopes NW. Descend 240 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 Sec. cor. with brass cap mkd.

1/4

S 35 S 36

1923

from which

A Hemlock, 6 ins. diam., bears N.20\*E., 18 lks. dist., mkd. 1/4 S 36 B T.

A Hemlock, 12 ins. diam., bears S.27\*W., 21 lks. dist., mkd. 1/4 S 35 B T.

Descend 335 ft. over NE. slope to

47.57 Lone Woman Creek, 65 lks. wide, C. W.

Ascend 640 ft. along broken SE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 25, 26, 35 and 36, with brass cap mkd.

T 29 S | R 2 E

S 26 | S 25

S 35 | S 36

1923

from which

A Pine, 12 ins. diam., bears N.48\*E., 29 lks.