

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 29 S., R. 2 E.

CHAINS

- 41.00 Spur, slopes E. Descend 100 ft. over N. slope.
- 44.08 Brook, 1 lk. wide, C. E. Ascend 280 ft. over SE. slope.
- 57.55 Spur, slopes SE. Descend 135 ft. over N. slope.
- 62.05 Brook, 1 lk. wide, course NE. Ascend 35 ft.
- 64.35 Spur, slopes SE. Descend 140 ft.
- 71.27 Creek, 7 lks. wide, course E. Ascend 175 ft. over S. slope.
- 78.90 Spur, slopes E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 23, 24, 25 and 26, with brass cap marked

T 29 S	R 2 E
S 23	S 24
S 26	S 25

1923

from which

- A Hemlock, 8 ins. diam., bears N.30°E., 2 lks. dist., marked T 29 S R 2 E S 24 B T.
- A Hemlock, 14 ins. diam., bears S.48°E., 24 lks. dist., marked T 29 S R 2 E S 25 B T.
- A Fir, 20 ins. diam., bears S.26°W., 47 lks. dist., marked T 29 S R 2 E S 26 B T.
- A Hemlock, 12 ins. diam., bears N.19°W., 13 lks. dist., marked T 29 S R 2 E S 23 B T.

Land, mountainous.

Soil, clay loam, and rocky; 2nd and 3rd rate.

Timber, Fir, Hemlock and Pine.

Undergrowth, Rhododendron, Fir, and Vine Maple.

-
- 40.00 S.89°45'E., on a random line bet. Secs. 24 and 25.
Set temp. ¼ Sec. cor.