

Subdivisions of T. 29 S., R. 2 E.

CHAINS


N.0\*1'W., bet. Secs. 23 and 24.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 660 ft. over irregular SE. slope to  $\frac{1}{4}$  Sec. cor.

32.84 Acker Divide Trail, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 ins. diam., 27 ins. in the ground, for  $\frac{1}{4}$  Sec. cor., with brass cap marked



from which

A Fir, 18 ins. diam., bears S.42\*E., 27 lks. dist., marked  $\frac{1}{4}$  S 24 B T.

A Fir, 10 ins. diam., bears N.27\*W., 33 lks. dist., marked  $\frac{1}{4}$  S 23 B T.

This  $\frac{1}{4}$  Sec. cor. is on the summit of divide bet. Buckeye Creek and S. Fork of S. Umpqua River, bears E. and W.


Descend 320 ft. over N. slope.

65.71 Brook, 1 lk. wide, C. NW. Ascend 50 ft.

71.50 Spur, slopes NW. Descend 40 ft.

75.72 Brook, 4 lks. wide, C. NW. Ascend gradually to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 13, 14, 23 and 24, with brass cap marked



from which

A Fir, 9 ins. diam., bears N.27\*E., 20 lks. dist., marked T 29 S R 2 E S 13 B T.

A Fir, 32 ins. diam., bears S.81\*E., 34 lks. dist., marked T 29 S R 2 E S 24 B T.

A Fir, 14 ins. diam., bears S.33\*W., 62 lks. dist.,