

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

57.70 Brook 1 lk. wide, course SE.
 63.00 Spur, slopes SE. Continue along E. slope.
 73.30 Draw, opens SE.
 76.40 Spur, slopes SE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins.
 in the ground, for cor. of secs. 26, 27, 34 and 35,
 with brass cap mkd.

T 29 S	R 2 E
S 27	S 26
S 34	S 35
1923	

from which

A pine, 40 ins. diam., bears N.35*E., 45 lks.
 dist., mkd. T 29 S R 2 E S 26 B T.

A cedar, 24 ins. diam., bears S.24*E., 35 lks.
 dist., mkd. T 29 S R 2 E S 35 B T.

A cedar, 28 ins. diam., bears S.47*W., 88 lks..
 dist., mkd. T 29 S R 2 E S 34 B T.

A fir, 48 ins. diam., bears N.57*W., 12 lks.
 dist., mkd. T 29 S R 2 E S 27 B T.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, fir, cedar, pine and hemlock.

Undergrowth, rhododendron, fir, and chinquapin.

East, on a random line bet. secs. 26 and 35.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.64 Intersect N. and S. line 23 lks. S. of the cor. of
 secs. 25, 26, 35 and 36.

Thence

S.89*50'W., on a true line bet. secs. 26 and 35.

Over mountainous land, through heavy timber and dense
 undergrowth.