

County Surveyor's Record, Douglas County, Oregon

43

Subdivision of T. 29 S., R. 2 E.

CHAINS

T 29 S	R 2 E
S 10	S 11
S 15	S 14
1926	

from which

A Douglas Fir, 28 ins. dia., bears N. $48\frac{1}{2}^*$ E., 22 lks. dist., marked T 29 S R 2 E S 11 BT.

A cedar, 36 ins. dia., bears S. $58\frac{1}{2}^*$ E., 57 lks. dist., marked T 29 S R 2 E S 14 BT.

A Douglas fir, 20 ins. dia., bears S. 17 * W., $18\frac{1}{2}$ lks. dist., marked T 29 S R 2 E S 15 BT.

A yellow pine, 22 ins. dia., bears N. 35* W., 35 lks. dist., marked T 29 S R 2 E S 10 BT.

Land, mountainous.

Soil, clay loam and rocky; 2nd rate.

Timber, Douglas fir, white fir, cedar and pine.

Undergrowth, young forest trees, rhododendron and vine maple.

N. 89* 56 ' E., on a random line, bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.92 Intersect N. and S. line, 10 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence,

West, on a true line, bet. secs. 11 and 14.

Over mountainous land, not very rough, through old burn, scattering timber and dense undergrowth.

Descend gradually over SW. slope.

4.00 Leave burn, enter heavy timber, bearing NW. and SE.

39.96 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 11
S 14
1926

from which

A white fir, 10 ins. dia., bears N. $38\frac{1}{2}^*$ W., 28 lks. dist., marked $\frac{1}{4}$ S 11 BT.

A Douglas fir, 28 ins. dia., bears S. 60 * W., 38 lks. dist., marked $\frac{1}{4}$ S 14 BT.

Descend 375 feet over W. slope to