

County Surveyor's Record, Douglas County, Oregon


Subdivision of T. 29 S., R. 2 E.

CHAINS

marked T 29 S R 2 E S 27 BT.
 A fir, 36 ins. dia., bears S. 67* E., 5 lks. dist.,
 marked T 29 S R 2 E S 34 BT.
 A fir, 28 ins. dia., bears S. 80* W., 27 lks. dist.,
 marked T 29 S R 2 E S 33 BT.
 A fir, 32 ins. dia., bears N. 65 * W., 60 lks. dist.,
 marked T 29 S.R 2 E S 28 BT.

Land, mountainous.
 Soil, clay loam and rocky; 2nd and 3rd rate.
 Timber, fir, cedar, pine and hemlock.
 Undergrwoth, rhododendron, fir and madrona.

East, on a random line, bet. secs. 27 and 34.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Intersect N. and S. line, 14 lks. S. of the cor. of secs.
 26, 27, 34 and 35.
 Thence,
 S. 89* 54' W., on a true line, bet secs. 27 and 34.
 Over mountainous land, through heavy timber and dense
 undergrowth.
 Ascend 200 ft. over E. slope.
 12.56 Trail, bears N. and S. on a spur, sloping S.
 Descend 400 ft. over SW. slope to $\frac{1}{4}$ sec. cor.
 26.15 Brook, 1 link wide, course NW.
 40.02 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A fir, 14 ins. dia., bears N. 88* E., 37 lks. dist.,
 marked $\frac{1}{4}$ S 27 BT.
 A cedar, 18 ins. dia., bears S. 59* E., 70 lks. dist.,
 marked $\frac{1}{4}$ S 34 BT.

Descend 275 ft. over W. slope.
 51.70 Brook, 4 lks. wide, course S. Ascend 275 ft.
 61.20 Spur, slopes S. Descend 150 ft.