


County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

62.10 Spur, slopes NW. Descend 430 ft., over N. slope to  
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap marked



from which

- A sugar pine, 9 ins. dia., bears N. 61 \* E., 11 lks., dist., marked T 29 S R 2 E S 15 BT.
- A Douglas fir, 9 ins. dia., bears S. 62 \* E., 49 lks. dist., marked T 29 S R 2 E S 22 BT.
- A sugar pine, 15 ins. dia., bears S. 33 \*W., 4 lks. dist., marked T 29 S R 2 E S 21 BT.
- A Douglas fir, 6 ins. dia., bears N. 65\* W., 69 lks. dist., marked T 29 S R 2 E S 16 BT.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, Douglas fir, white fir, sugar pine and hemlock.

Undergrowth, rhododendron, chinquapin and vine maple.

N. 89\* 46' E., on a random line, bet. Secs. 15 and 22.

40.00 Set temp. 1/4 sec. cor.

79.84 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence,

S. 89\* 49' W., on a true line, bet. secs. 15 and 22.

Over mountainous land, through heavy timber and dense undergrowth.


Descend 120 ft. over NW. slope.

5.60 Dry gulch, course NW. Ascend 35 ft., over NE. slope.

10.00 Spur, slopes N. Descend 175 ft., over NW. slope.

29.30 Draw, opens N. Ascend 140 ft., over NE. slope.

39.92 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked



from which