

## County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

A fir, 14 ins. dia., bears N. 56\* E., 31 lks. dist.,  
marked  $\frac{1}{4}$  S 15 BT.

A cedar, 12 ins. dia., bears S. 41\* E., 20 lks. dist.,  
marked  $\frac{1}{4}$  S 22 BT.

40.25 Dry draw, opens NW.

42.00 Low spur, slopes N. Descend 70 ft., over NW. slope.

49.25 Creek, 10 lks. wide, course NW. Ascend 100 ft.

58.00 Spur, slopes N. Descend 180 ft.

68.50 Dry gulch, course N. 25\*W. Ascend 130 ft. over NE. slope.

74.00 Spur, slopes NW. Descend 50 ft. to

79.84 The cor. of secs. 15, 16, 21 and 22.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, rhododendron, vine maple and young trees.

-----  
N. 0\* 2' W., bet. secs. 15 and 16.

Over mountainous land, through heavy timber and dense  
undergrowth.

Descend 120 ft. over N. slope.

4.57 Brook, 1 link wide, course N.30\*W. Ascend 30 ft.

7.50 Low spur, slopes N.60\*W. Descend 100 ft. over NW. slope.

9.44 Buckeye Creek, 10 lks. wide, course W. Ascend 185 feet.

36.50 Spur, slopes W. Descend 60 ft., over N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S 16 S 15  
1926

from which

A fir, 8 ins. dia., bears S. 50\* E., 13 lks. dist.,  
marked  $\frac{1}{4}$  S 15 BT.

A fir, 4 ins. dia., bears S. 25\* W., 8 lks. dist.,  
marked  $\frac{1}{4}$  S 16 BT.

Descend 130 ft. over N. slope.

43.15 Fork of Buckeye Creek, 10 lks. wide, very little water,  
course W. Ascend 225 ft., over S. slope.

56.00 Spur, slopes SW. Ascend gradually along W. slope.