

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

70.00 Brook, 4 lks. wide, course SW. Ascend 120 ft., over SW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked

T 29 S	R 2 E
S 9	S 10
S 16	S 15
1926	

from which

A Douglas Fir, 18 ins. dia., bears N. 44 $\frac{1}{2}$ \* E., 96 lks. dist., marked T 29 S R 2 E S 10 BT.

A sugar pine, 4 ins. dia., bears S. 82\* E., 18 lks. dist., marked T 29 S R 2 E S 15 BT.

A Douglas fir, 24 ins. dia., bears S. 20\* W., 52 lks. dist., marked T 29 S R 2 E S 16 BT.

A Douglas fir, 10 ins. dia., bears N. 46\* W., 56 lks. dist., marked T 29 S R 2 E S 9 BT.

Land, mountainous.

Soil, rocky clay loam; 2nd and 3rd rate.

Timber, Douglas fir, white fir, sugar pine, incense cedar and hemlock.

Undergrowth, vine maple, chinquapin, yew and young forest trees.

N. 89\* 49' E., on a random line, bet. secs. 10 and 15.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect N. and S. line, 16 lks. N. of the cor. of secs. 10, 11, 14 and 15.

Thence,

S. 89\* 56' W., on a true line, bet. secs. 10 and 15.

Over mountainous land, through heavy timber and medium undergrowth.

Ascend 70 ft., over SE. slope.

10.00 Spur, slopes S. Descend 350 ft., over SW. slope., to  $\frac{1}{4}$  sec. cor.

29.25 Dry gulch, course SW.

36.05 Spring branch, 1 link wide, course SW. Enter bottom land, bearing NW. and S.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the