

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

dist., marked  $\frac{1}{4}$  S 10 BT.

A Douglas fir, 16 ins. dia., bears N. 75\* W., 21 lks.

dist., marked  $\frac{1}{4}$  S 9 BT.

This cor. is in a draw, opening NE.

Ascend 50 ft., over SE. slope.

44.00 Spur, slopes NE. Descend 460 ft., over NE. slope to sec. corner.

58.00 Ravine, with very little water, course E. Ascend 40 ft.

61.00 Spur, slopes E. Descend, over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T 29 S	R 2 E
S 4	S 3
S 9	S 10
1926	

from which

A hemlock, 5 ins. dia., bears N. 10\* E., 32 lks.

dist., marked T 29 S R 2 E S 3 BT.

A Douglas fir, 24 ins. dia., bears S. 74\*E., 44 lks.

dist., marked T 29 S R 2 E S 10 BT.

A Douglas fir, 24 ins. dia., bears S. 10 \* W., 16 lks.

dist., marked T 29 S R 2 E S 9 BT.

A Douglas fir, 12 ins. dia., bears N. 78\* W., 48 $\frac{1}{2}$  lks.

dist., marked T 29 S R 2 E S 4 BT.

Land, mountainous.

Soil, on S. slope, rocky; on N. slope clay loam; 3rd and 2nd rate.

Timber, Douglas fir, sugar pine, yellow pine and cedar.

Undergrowth, yew, rhododendron and vine maple.

N. 89\* 56' E., on a random line, bet. secs. 3 and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.34 Intersect N. and S. line, 2 lks. N. of cor. of secs. 2, 3, 10 and 11.

Thence,

S. 89\* 57' W., on a true line, bet. secs. 3 and 10.

Over mountainous land, through heavy timber and dense