

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 29 S., R. 2 E.

CHAINS

- Ascend 575 ft., over E. and SE. slope.
- 24.50 Spur, slopes S. Descend 260 ft., over W. and SW. slope.
- 40.07 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
- $\frac{1}{4}$       S 28  
           S 33  
 1923                      from which
- A fir, 8 ins. dia., bears N. 87° W., 42 lks. dist., marked  $\frac{1}{4}$  S 28 BT.
- A fir, 48 ins. dia., bears S. 54° E., 168 lks. dist., marked  $\frac{1}{2}$  S. 33 BT.
- Descend 260 ft. to
- 60.86 Brook, 1 link wide, course SW. Descend gradually to
- 80.14 The corner of secs. 28, 29, 32 and 33.
- Land, mountainous.
- Soil, rocky clay loam; 2nd and 3rd rate.
- Timber, fir, pine and cedar.
- Undergrowth, rhododendron and vine maple.
- 
- N. 0° 3' W., bet. secs. 28 and 29.
- Over mountainous land, through heavy timber and medium undergrowth.
- Ascend 775 ft., over irregular, rocky, S. slope.
- 28.30 Divide bet. S. Fork of S. Umpqua River, and Buckeye Creek bears E. and W. Descend 225 ft. to  $\frac{1}{4}$  sec. cor.
- 32.60 Acker Divide Trail, bears E. and W.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
- $\frac{1}{4}$   
 S 29 | S 28  
 1923                      from which
- A fir, 14 ins. dia., bears N. 74° E., 24 lks. dist., marked  $\frac{1}{4}$  S 28 BT.
- A Fir, 14 ins. dia., bears N. 50° W., 23 lks. dist., marked  $\frac{1}{4}$  S 29 BT.
- Descend 65 ft.
- 42.67 Brook, 2 lks. wide, course NW. Ascend gradually.