

62
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 21
S 28
1923

from which

A fir, 9 ins. dia., bears N. 18 * E., 4 lks. dist.,
marked $\frac{1}{4}$ S 21 BT.

A pine, 26 ins. dia., bears S. 15* E., 21 lks. dist.,
marked $\frac{1}{4}$ S 28 BT.

Descend 500 ft., over NW. slope.

79.90 The cor. of secs. 20, 21, 28 and 29.

Land, mountainous.

Soil, rocky clay loam; 2nd and 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, rhododendron, vine maple and fir.

N. 0* 3' W., bet. secs. 20 and 21.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 110 ft., over S. slope.

7.50 Summit of spur, bears E. and W. Descend 750 ft., over N.
slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S 20 | S 21
1926

from which

A hemlock, 6 ins. dia., bears S. 51* E., 6 lks. dist.,
marked $\frac{1}{4}$ S 21 BT.

A fir, 50 ins. dia., bears West, 20 lks. dist.,
marked $\frac{1}{4}$ S 20 BT.

A basalt face of bluff in mountainside, 6x 4 ft.
above ground, bears S. 38* W., $3\frac{1}{2}$ lks. dist.,
marked X B $\frac{1}{4}$ S 20.

Descend 75 ft., over N. slope to

42.00 Ravine, very little water, course N. 10* W., from S. 30* E.

Descend 250 ft., along E. side of ravine.

48.05 Dry ravine, course W. Ascend 300 ft. over SW. slope.