


Subdivision of T. 29 S., R. 2 E.

CHAINS

68.00 Summit of spur, bears E. and W. Descend 280 ft., over NE. slope.

78.56 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for witness corner to the corner of sections 16, 17, 20 and 21, with brass cap marked



from which

A cedar, 14 ins. dia., bears N. 28 * E., 33 lks. dist., marked W C T 29 S R 2 E S 21 BT

A Douglas fir, 26 ins. dia., bears S. 25* E., 22 lks. dist., marked W C T 29 S R 2 E S 21 BT.

A cedar, 6 ins. dia., bears S. 65* W., 17½ lks. dist. marked W C T 29 S R 2 E S 20 BT.

A Douglas fir, 18 ins. dia., bears N. 8½* W., 46 lks. dist., marked W C T 29 S R 2 E S 20 BT.

78.80 Face of bare bluff sloping E., bears E. and W.

80.00 Point for cor. of secs. 16, 17, 20 and 21, falls on steep bare face of rock where it is impracticable to build a permanent monument; or to make a lasting and conspicuous mark, though not entirely inaccessible.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, Douglas fir, white fir, and sugar pine.

Undergrowth, rhododendron, vine maple, hazel, chinquapin and white fir.

N. 89* 53' E., on a random line, bet. secs. 16 and 21.

40.00 Set temp. ¼ sec. cor.

80.20 Intersect N. and S. line, 33 lks. N. of the cor. of secs. 15, 16, 21 and 22.

Thence,

N. 89* 53' W., on a true line, bet. secs. 16 and 21.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend gradually, over NE. slope to