

64  
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

- 3.00 Low spur, slopes N. Descend 110 ft., over NW. slope.
- 6.00 Draw, opens N. Continue along broken N. slope.
- 25.00 Spur, slopes N. 60\* W. Descend 320 ft., over SW. slope.
- 38.80 Brook, 5 lks. wide, course N. 70\* W. Continue along steep bank, sloping N. to
- 40.10 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
 

$$\frac{1}{4} \frac{S \ 16}{S \ 21}$$

1926

from which

A fir, 30 ins. dia., bears N. 50\* W., 46 lks. dist., marked  $\frac{1}{4}$  S 16 BT.

A fir, 36 ins. dia., bears S. 50\* W., 46 lks. dist., marked  $\frac{1}{4}$  S 21 BT.

Continue along broken, steep N. and NW. slope.
- 44.10 Spur, slopes N. Descend 120 ft., over NW. slope.
- 48.91 Spring branch, very little water, course NW. Ascend 200 ft., over NE. slope.
- 56.70 Spur, slopes N. Descend 60 ft.
- 60.13 Dry gulch, course N. Ascend 160 ft., over NE. slope.
- 69.00 Spur, slopes N. Descend 210 ft., over N. slope.
- 73.25 Dry gulch, course N. 60\* W. Ascend gradually along steep N. slope.
- 75.50 Spur, slopes N. Descend 100 ft., over NW. slope.
- 77.40 Dry gulch, course N. Ascend 160 ft., over E. slope.
- 78.00 Face of bare rock, bears N. and **SW**.
- 80.20 The point for cor. of secs. 16, 17, 20 and 21.
  - Witness cor. bears S. 0\* 3' E., 144 lks. dist.

Land, mountainous.

Soil, rocky clay loam; 2nd and 3rd rate.

Timber, Douglas fir, white fir, and sugar pine.

Undergrowth, rhododendron, chinquapin and vine maple.

---

From true cor. point,  
N. 0\* 3' W., bet. secs. 16 and 17.