

Subdivisions of T. 29 S., R. 2 E.

CHAINS	Over mountainous land, bare surface rock, sloping E.												
2.00	Spur, slopes NE. Enter heavy timber and dense undergrowth, bearing NE. and SW. Descend 410 ft. over N. slope.												
10.30	Brook, 4 lks. wide, course NW. Ascend 60 ft.												
13.20	Spur, slopes W. Descend 90 ft. over N. slope.												
16.00	Falls on a boulder, about 60x40x30 ft.												
17.10	Buckeye Creek, 50 lks. wide, course S.60*W. Ascend steep S. slope. Enter recent burn, bearing E. and W.												
20.86	150 ft. above Buckeye Creek, perpendicular bluff 150 ft. high, facing S.20*E. Offset East 60 lks. Thence, N.0*3'W., 4.07 chs. Thence, West 60 lks. to the line at 24.93 chs.												
24.93	Point on line, 310 ft. above foot of bluff. Continue to ascend, over SE slope.												
35.60	Spur, 450 ft. above Buckeye Creek, slopes E. Descend 75 ft. over NE slope.												
36.80	Leave recent burn, bearing E. and W.												
38.30	Ravine, C. E. Ascend 40 ft. over SE. slope to												
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ Sec. cor., with brass cap marked <div style="text-align: center;"> <table border="0"> <tr> <td>S 17</td> <td style="border: 1px solid black; padding: 0 5px;">↑</td> <td>S 16</td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 0 5px;">1926</td> <td></td> </tr> </table> </div> <p style="text-align: right; margin-right: 100px;">from which</p> <p style="margin-left: 40px;">A Douglas Fir, 10 ins. diam., bears N.22$\frac{1}{2}$*E., 35$\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S 16 B T. A Cedar, 12 ins. diam., bears S.15*W., 16$\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S 17 B T.</p>	S 17	↑	S 16		1926							
S 17	↑	S 16											
	1926												
	Ascend 20 ft. over SE. slope.												
41.25	Spur, slopes E. Descend 60 ft. over N. slope.												
42.87	Dry gulch, course NE. Ascend 160 ft. over SE. slope.												
58.40	Spur, slopes SE. Descend 70 ft.												
65.90	Dry gulch, C. S.30*E. Ascend 360 ft. over SW. slope.												
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 8, 9, 16 and 17, with brass cap marked <div style="text-align: center;"> <table border="0"> <tr> <td>T 29 S</td> <td style="border: 1px solid black; padding: 0 5px;"> </td> <td>R 2 E</td> </tr> <tr> <td>S 8</td> <td style="border: 1px solid black; padding: 0 5px;"> </td> <td>S 9</td> </tr> <tr> <td style="border-top: 1px solid black;">S 17</td> <td style="border-top: 1px solid black; border: 1px solid black; padding: 0 5px;"> </td> <td style="border-top: 1px solid black;">S 16</td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 0 5px;">1926</td> <td></td> </tr> </table> </div> <p style="text-align: right; margin-right: 100px;">from which</p>	T 29 S		R 2 E	S 8		S 9	S 17		S 16		1926	
T 29 S		R 2 E											
S 8		S 9											
S 17		S 16											
	1926												