

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 29 S., R. 2 E.

## CHAINS

- 79.70 The cor. of secs. 4, 5, 8 and 9.  
Land, mountainous.  
Soil, clay loam; 2nd rate.  
Timber, Douglas fir, and sugar pine.  
Undergrowth, rhododendron, vine maple and white fir.
- 
- From the corner of secs. 5, 6, 31 and 32, on S. bdy. of Tp., hereinbefore described;  
N. (± 4' W., bet. secs. 31 and 32.  
Over bottom land, through heavy timber and dense undergrowth.
- 4.34 Left bank of S. Fork of S. Umpqua River, course SW.  
4.85 Right bank of same. Ascend 700 ft. over S. slope.  
37.70 Spur, slopes SW. Descend gradually to  
40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked.
- |  |            |
|--|------------|
| $\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \text{ }   \text{ } \text{S } 32 \\ \hline 1923 \end{array}$ | from which |
|--|------------|
- A madrona, 10 ins. dia., bears S. 18\* E., 23 lks. dist., marked  $\frac{1}{4}$  S 32 BT.  
A madrona, 8 ins. dia., bears N. 42\* W., 32 lks. dist., marked  $\frac{1}{4}$  S 31 BT
- Descend gradually along W. slope.
- 42.50 Foot of descent, bears NE. and SW. Ascend 630 ft., over S. slope to the sec. cor.  
72.71 Rocky draw, opens SW. Ascend steep, rocky S. slope to  
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap marked
- |   |            |
|---|------------|
| $\begin{array}{c} \text{T } 29 \text{ S }   \text{ R } 2 \text{ E} \\ \text{S } 30 \text{ }   \text{ S } 29 \\ \hline \text{S } 31 \text{ }   \text{ S } 32 \\ \hline 1923 \end{array}$ | from which |
|---|------------|
- A fir, 14 ins. dia., bears N. 62\* E., 26 lks. dist., marked T 29 S R 2 E S 29 BT.  
A fir, 20 ins. dia., bears S. 84\* E., 22 lks. dist., marked T 29 S R 2 E S 32 BT.  
A fir, 20 ins. dia., bears S. 21\* W., 20 lks. dist.,