

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

West, on a random line, bet. secs. 30 and 31.

40.00 Set temp. 1/4 sec. cor.

76.52 Intersect west Bdy. of Tp. at the cor. of secs. 25, 30, 31 and 36, which is a basalt stone, set firmly, marked and witnessed as described by the surveyor general.

Thence,

East, on a true line, bet. secs. 30 and 31.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 300 ft., over SW. slope to 1/4 sec. cor.

15.90 A trail, bears NW. and SE.

36.52 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 30  
S 31  
1923

from which

A fir, 7 ins. dia., bears N. 9\* E., 7 lks. dist., marked 1/4 S 30 BT.

A madrona, 16 ins. dia., bears S. 3\* E., 11 lks. dist., marked 1/4 S 31 BT.

Ascend 500 ft., over SW. slope to

76.52 The cor. of secs. 29, 30, 31 and 32.

Land, mountainous.

Soil, clay loam and rocky; 2nd, 3rd, and 4th rate.

Timber, fir, cedar and pine.

Undergrowth, fir and rhododendron.

N. 0\* 4' W., bet., secs. 29 and 30.

Over mountainous land, through heavy timber and medium undergrowth.

Ascend 250 ft., over S. and SW. slope.

12.00 Divide bet. S. Fork of S. Umpqua River and Buckeye Creek, bears E. and W. Acker Divide Trail, same bearing.

Descend 120 ft., over N. slope.

32.81 Brook, 3 lks. wide, course NW. Continue along W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the