

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   $\frac{S\ 18}{S\ 19}$   
1926

from which

A Douglas fir, 7 ins. dia., bears North,  $18\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S 18 LT.

A Douglas fir, 34 ins. dia., bears S.  $55^{\circ}$  W.,  $12\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S 19 BT.

Ascend 225 ft., over W. slope.

58.10 Spur, slopes N. Descend 125 ft., over NE. slope.

76.40 The cor. of secs. 17, 18, 19, and 20.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, Douglas fir, white fir and sugar pine.

Undergrowth, rhododendron, vine maple and chinquapin and hazel.

N.0\* 4' W., bet. secs. 17 and 18.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 440 ft., over broken N. slope.

15.08 Buckeye Creek, 25 lks. wide, course NW. Continue over narrow bottom.

16.20 Leave bottom, bearing E. and W. Ascend 360 ft., over SW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S 18 | S 17  
1926

from which

A Douglas fir, 24 ins. dia., bears N.  $15^{\circ}$  E., 34 lks. dist., marked  $\frac{1}{4}$  S 17 BT.

A Douglas fir, 24 ins. dia., bears S.  $75^{\circ}$  W., 7 lks. dist., marked  $\frac{1}{4}$  S 18 BT.

Ascend 1050 ft., over SW. and S. slope.

75.90 Sharp spur, slopes W. Descend 150 ft., over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the