

Subdivision of T. 29 S., R. 2 E.

CHAINS

ground, for cor. of secs. 7, 8, 17 and 18, with brass cap marked

T 29 S	R 2 E
S 7	S 8
S 18	S 17
1926	

from which

A Douglas fir, 10 ins. dia., bears N. 38* E., 29 lks. dist., marked T 29 S R 2 E S 8 BT.

A Douglas fir, 14 ins. dia., bears S. 22* E., 25 lks. dist., marked T 29 S R 2 E S 17 BT.

A Douglas fir, 12 ins. dia., bears S. 51* W., 27 lks. dist., marked T 29 S R 2 E S 18 BT.

A Douglas fir, 14 ins. dia., bears N. 14* W., 25 lks. dist., marked T 29 S R 2 E S 7 BT.

Land, mountainous.

Soil, rocky clay loam; 3rd and 2nd rate.

Timber, fir, pine and cedar.

Undergrowth, vine maple, chinquapin, hazel and fir.

S. 89* 40' E., on a random line, bet. secs. 8 and 17.

40.00 Set temp. 1/2 sec. cor.

79.66 Intersect N. and S. line, 14 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence,

N. 89* 46' W., on a true line, bet. secs. 8 and 17.

Over mountainous land, through heavy timber and medium undergrowth.

6.55 Dry draw, opens S. Ascend 100 ft.

10.30 Spur, slopes S. Descend 275 ft., over SW. slope.

29.00 Dry gulch, course S. 30* W. Ascend 100 ft.

35.00 Spur, slopes S. Descend 100 ft., over W. slope to

39.83 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4	S 8
	S 17
1926	

from which

A Douglas fir, 40 ins. dia., bears N. 30*W., 55 lks. dist., marked 1/4 S 8 BT.

A Douglas fir, 30 ins. dia., bears S. 66* E., 54 lks.