

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS

dist., marked  $\frac{1}{4}$  S 17 BT.

- 41.50 Dry ravine, course S. Ascend 260 ft., over E. slope.
- 52.33 Spur, slopes S. Continue along broken S. slope.
- 70.00 Spur, slopes SW. This is the divide between Buckeye Creek and S. Umpqua River. Descend 125 ft., over NW. slope.
- 79.66 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous.

Soil, clay loam and rocky; 2nd and 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, rhododendron, fir, vine maple and hazel.

N. 89\* 46' W., on a random line, bet. secs. 7 and 18.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.

- 76.28 Intersect W. bdy. of Tp., 31 lks. N. of the cor. of secs. 7, 12, 13 and 18; which is an iron post, 2 ins. dia., 12 ins. above the ground, firmly set, marked and witnessed as described in the notes of E. bdy. of T. 29 S., R 1 E.

Thence,

East, on a true line, bet. secs. 7 and 18.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 40 ft., over SE. slope.

- 2.25 Dry ravine, course S. Ascend 140 ft., over SW. slope.

- 8.00 Summit of spur, slopes NW. This is divide bet. Buckeye Creek, and S. Umpqua River.

Descend 350 ft., over NE. slope.

- 20.00 Draw, opens N. Ascend 220 ft., over NW. slope to

- 36.28 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$  S 7  
S 18  
1926

from which

A Douglas fir, 16 ins. dia., bears N. 22 \* E., 49 lks. dist., marked  $\frac{1}{4}$  S 7 BT.

A sugar pine, 32 ins. dia., bears S. 34\* W., 29 lks. dist., marked  $\frac{1}{4}$  S 18 BT.

Ascend 75 ft., over W. slope.