

84
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 E.

CHAINS	
	<p>A Douglas fir, 10 ins. diam., bears N. 57*E., 67 lks. dist., mkd. $\frac{1}{4}$ S 6 B T</p> <p>A sugar pine, 8 ins. diam., bears S. 33$\frac{1}{2}$*E., 68 lks. dist., mkd. $\frac{1}{4}$ S 7 B T</p>
36.45	Shallow dry gulch, course NW. Ascend gradually.
60.96	Corner No. 2, of H.E.S. No. 192, a quartzite stone, 15x12x10 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears S., 96 lks. dist.
74.32	Brook, 3 lks. wide, course NW.
76.32	The corner of sections 5, 6, 7 and 8. Land, heavily rolling. Soil, clay loam; 2nd rate . Timber, fir, pine and cedar. Undergrowth, rhododendron, chinquapin, vinemaple and fir.
40.00	N.0*1'W., on a random line, bet. secs. 5 and 6. Set temp. $\frac{1}{4}$ sec. cor.
79.50	Intersect N. bdy. of Tp., 21 lks. E. of the cor. of secs. 5,6,31 and 32, as hereinbefore described. Thence, S.0*10'E., on a true line, bet. secs. 5 and 6. Over mountainous land, through heavy timber and dense undergrowth. Ascend 880 ft., over N. and NE. slope, to $\frac{1}{4}$ sec. cor.
27.33	Brook, 2 lks. wide, course N.30*E., 580 ft. above sec. cor.
39.50	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \downarrow \\ \text{S } 6 \text{ S } 5 \\ \text{1926} \end{array}$
	From which
	<p>A Douglas fir, 22 ins. diam., bears N. 44*E., 22 lks. dist., mkd. $\frac{1}{4}$ S 5 B T</p> <p>A Douglas fir, 48 ins. diam., bears S. 45*W., 18 lks. dist., mkd. $\frac{1}{4}$ S 6 B T</p> <p>Ascend 125 ft., over N. slope.</p>