

County Surveyor's Record, Douglas County, Oregon
 Resurvey of Part of the West Boundary, Survey of South,
 East and North Boundaries, and Subdivisions of T. 29 S.,
 R. 3 E., as executed by Herbert N. Raymond. U.S.C.E.,
 under special instructions.

Dated Dec., 27th 1920.

CHAINS	Retracement of West Boundary.
	From the cor. of secs. 19,24,25 and 30 on W. Bdy of the Township.
	North, retracing bet. secs. 19 and 24.
39.32	The $\frac{1}{4}$ sec. cor.
79.06	The cor. of secs. 13,18,19 and 24.
	The bearing and length of the S. half mile is N.,39.32 chs. and the N. half is N. 39.74 chs.
	From the cor. of secs. 13,18,19 and 24.
	North, retracing bet. secs. 13 and 18.
39.61	Fall, 12 lks, E. of the $\frac{1}{4}$ sec. cor.
40.94	Offset 7.26 chs. W. thence N. 17.02 chs.
57.96	Offset 7.79 chs. E., thence N. 21.60 chs.
79.56	The cor. of secs. 7,13,12 and 18.
	The bearing and length of the S. half mile is N.0*10'W., 39.61 chs. and the N. half is N.0*56'E., 39.96 chs.
	From the cor. of secs.,7,12,13 and 18.
	North Retracing bet. secs. 7 and 12.
39.83	The $\frac{1}{4}$ sec. cor.
79.98	The cor. of secs. 1,6,7 and 12.
	The bearing and length of the S. half mile is N.39.83 chs. and the N. half is N.40.15 chs.
	From the cor. of secs. 1,6,7 and 12.
	North, retracing bet. secs.1 and 6.
40.34	The $\frac{1}{4}$ sec. cor.
80.77	The cor. of Tps. 28 and 29 S., Rs 2 and 3 E.
	The bearing and length of the S. half mile is N. 40.34 chs. and the N. half is 40.43 chs.
	Resurvey of the West Boundary.
	From the cor of secs. 19,24,25 and 30, which is an iron post 2 ins. in diam., 12 ins. above the ground, with brass cap marked and witnessed as described in