

County Surveyor's Record, Douglas County, Oregon

Resurvey of the West Boundary of T. 29 S., R. 3 E.

CHAINS	the field notes of the original survey.
	North, bet. secs. 19 and 24.
	Over mountainous land, through medium timber and medium undergrowth.
	Asc. 530 ft. over S. slope.
16.50	Spur, slopes SW., asc. 370 ft. over SW. slope to
39.32	The $\frac{1}{4}$ sec. cor. established for secs. 19 and 24, which is an iron post, 2 ins. in diam., 10 ins. above the ground, with brass cap marked and witnessed as described in the field notes of the original survey, excepting the bearing of the West tree. I obliterate all marks on the E. side of the brass cap and on bearing trees E. of the line and mark new bearing trees W. of the line., from the cor.
	A pine, (new) 5 ins. in diam., bears S.67*W., 58 lks. dist., marked $\frac{1}{4}$ S 24 B T.
	A Fir, (old) 50 ins. in diam., bears N.73*W., 25 lks. dist., marked $\frac{1}{4}$ S 24 B T.
	This cor. will hereafter refer to sec. 24 only.
	Asc. 15 ft. over S. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground, to bed rock, and build a mound of stone, 24 ins. base, 9 ins. high around the post, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap marked
	$\frac{1}{4}$ S19 1927
	from which
	A Cedar, 7 ins. in diam., bears N.23*E., 55 lks. dist., marked $\frac{1}{4}$ S 19 B T.
	A Fir, 50 ins. in diam., bears S.81*E., 10 lks. dist., marked $\frac{1}{4}$ S 19 B T
	Asc. 130 ft. over SE. slope.
49.50	Spur, slopes SW., desc. 30 ft. over NW. slope.
58.00	Foot of desc. on W. slope, asc. 115 ft. over SW. slope.