

County Surveyor's Record, Douglas County, Oregon

Resurvey of West Bdy of T. 29 S., R. 3 E.

CHAINS
71.00


Spur, slopes W., desc. 25 ft. over NW. slope.

76.25

Draw, drains SW., asc. 25 ft. over S. slope to

79.06

The cor. established for secs. 13, 18, 19 & 24. which is an iron post, 2 ins. in diam., 10 ins above the ground, with brass cap marked and witnessed as described in the field notes of the original survey. I obliterate all marks on E. side of brass cap and on bearing trees E. of line, and remark brass cap.



From which the original bearing trees.

A Fir, 9 ins. in diam., bears S.82*W., 41 lks. dist. marked T 29 S R 2 E S 24 B T.

A Cedar, 16 ins. in diam., bears N.35*W., 31 lks. dist., marked T 29 S R 2 E S 13 B T.

This cor. will hereafter refer to secs. 13 & 24 only.

Land., Mountainous.

Soil., Sandy & rocky loam., 2nd & 3rd rate.

Timber., Fir, pine & cedar.

Undergrowth., Willow, huckleberry, vine maple, small fir and pine.

N.0*10'W., bet. secs. 13 & 19.

Over mountainous land, through medium timber & medium undergrowth.. asc. 25 ft. over SW. slope to

0.94

Point 80.00 chs. in northing from cor. of secs. 19 & 30.

Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground, for cor. of secs. 18 & 19 only, with brass cap marked

