

County Surveyor's Record, Douglas County, Oregon

Reurvey of West Boundary of T. 29 S., R. 3 E.

CHAINS

From which

A Fir, 12 ins. in diam., bears N.36*E., 34 lks. dist.
marked T 29 S R 3 E S 18 B T.

A Fir, 14 ins. in diam., bears S.57 $\frac{1}{2}$ *E., 41 lks.,
dist., marked T 29 S R 3 E S 19 B T.

Thence bet, secs. 13 & 18.

Asc. 575 Ft. over S. & SE. slopes to $\frac{1}{4}$ sec. cor.

30.85 Forest Service Trail, bears E. & W.

31.20 Forest Service Trail, bears NW. & SE.

39.61 The $\frac{1}{4}$ sec. cor. established for secs. 13 & 18, which is
an iron post, 1 in. in diam., 10 ins. above the ground,
with brass cap marked and witnessed approximately as
described in the field notes of the original survey. I
obliterate all marks on the E. side of the brass cap
and on the bearing tree E. of line, and mark a new
bearing tree W. of line, from the cor.

A Fir, (new) 5 ins. in diam., bears S.34*W., 26 lks.
dist., marked $\frac{1}{4}$ S 13 B T.

A Fir, (old) 8 ins. in diam., bears S.65*W., 21 lks.
dist., marked $\frac{1}{4}$ S 13 B T.

This cor. will hereafter refer to sec. 13 only.

Thence

N.0*56'E.,

Asc. 25 ft. over SE. slope to

1.33 Point 40.00 chs. in northing from cor. of secs. 18 & 19
only.

Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of sec. 18 only, with brass
cap marked

$\frac{1}{4}$ S 18
1927

From which

A Fir, 30 ins. in diam., bears N.70*E., 16 lks. dist.
marked $\frac{1}{4}$ S 18 B T.