

Resurvey of West Boundary of T.29 S., R. 3 E.

CHAINS

marked

T 29 S	T 29 S
R 2 E	S 7
S 13	S 18
1927	R 3 E

From which

A Cedar, 11 ins. in diam., bears N.78\*E., 30 lks. dist., marked T 29 S R 3 E S 7 B T.

A Fir, 18 ins. in diam., bears S.33\*E., 30 lks. dist., marked T 29 S R 3 E S 18 B T

Thence

Bet. secs. 7 & 12.

Desc. 220 ft. over N. slope.

12.00 Draw, drains NE., asc. 70 ft. over SE. slope.

19.00 Low spur, slopes NE., desc. 280 ft. over N. slope to

39.83 The 1/4 sec. cor. established for secs. 7 & 12, which is an iron post, 1 in. in diam., 12 ins. above the ground, with brass cap marked and witnessed as described in the field notes of the original survey. I obliterated all marks on the E. side of the brass cap and on bearing trees E. of the line, and mark a new bearing tree W. of the line, from the cor.

A Fir, (old) 34 ins. in diam., bears S.39\*W., 24 lks. dist., marked 1/4 S 12 B T.

A Fir, (new) 16 ins. in diam., bears N.19\*W., 40 lks. dist., marked 1/4 S 12 B T.

This cor. will hereafter refer to secs. 12 only.

Desc. 15 ft. over N. slope to

41.38 Point 40.00 chs. in northing from the cor. of secs. 7 & 18 only.

Set an iron post, 3 ft. long. 1 in. in diam., 30 ins. in the ground, for 1/4 sec. cor of sec. 7 only with brass cap marked

1/4 S 7
1927