

County Surveyor's Record, Douglas County, Oregon

Resurvey of the West Boundary of T. 29 S., R. 3 E.

CHAINS

From which

A Fir, 8 ins. in diam., bears N.6*E., 50 lks. dist.
marked T 29 S R 3 E S 6 B T.

A Cedar, 24 ins. in diam., bears S.13*E., 68 lks.
dist., marked T 29 S R 3 E S 7 B T.

Thence bet. secs. 1 & 6.

Asc. 30 ft. over SE. slope.

4.60 Low spur, slopes NE., desc. 160 ft. over NE. slope to
next spur.

18.00 Forest Service Trail, bears NE. & SW.

26.75 Spur, slopes NE., desc. 550 ft. over NW. slope.

38.50 Draw, drains NW. asc. 45 ft. over SW. slope to

40.34 The $\frac{1}{4}$ sec. cor. established for secs. 1 & 6, which is an
iron post 1 in. in diam., 11 ins. above the ground, with
brass cap marked & witnessed as described in the field
notes of the original survey, I obliterated all marks
on the E. side of the brass cap and on the bearing trees
E. of the line, and mark a new bearing tree W. of the
line, from the cor.

A Fir, (old) 26 ins. in diam., bears N.38*W., 31 lks.
dist., marked $\frac{1}{4}$ S 1 B T.

A Cedar, (new) 18 ins. in diam., bears N.8*W., 73 lks.
dist., marked $\frac{1}{4}$ S 1 B T.

Thence over W. slope to

41.40 Point 40.00 chs. on northing from the cor of secs. 6 & 7
only

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
in the ground, for $\frac{1}{4}$ sec. cor of sec. 6 only, with brass
cap marked

1926
1927

From which

A Cedar, 12 ins. in diam., bears N.26*E., 16 lks.
dist., marked $\frac{1}{4}$ S 6 B T.