

## County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 3 E.,

CHAINS  
22.00

Draw, drains NE., asc. 210 ft. over SE. slope to

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
$$\frac{1}{4} \begin{array}{l} S 36 \\ S 1 \\ 1927 \end{array}$$

from which

A Fir, 10 ins. in diam., bears N.31\*E., 127 lks. dist., marked  $\frac{1}{4}$  S 36 B T.A Fir, 26 ins. in diam., bears S.38\*W., 17 lks. dist., marked  $\frac{1}{4}$  S 1 B T.

Thence over S. slope.

41.80

Draw, drains SE., asc. 240 ft. over NE. slope.

52.20

Spur, slopes SE., asc. 80 ft. over SE. slope.

61.00

Spur, slopes S., thence over broken S. slope.

73.50

Spur, slopes S., desc. 45 ft. over SW. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap marked.

$$\begin{array}{l} T 29 S R 3 E \\ S 35 | S 36 \\ S 2 | S 1 \\ T 30 S \\ 1927 \end{array}$$

from which

A Fir, 24 ins. in diam., bears N.43\*E., 42 lks. dist., marked T 29 S R 3 E S 36 B T.

A pine, 48 ins. in diam., bears S.34\*E., 47 lks. dist., marked T 30 S R 3 E S 1 B T.

A Fir, 18 ins. in diam., bears S.12\*W., 47 lks. dist., marked T 30 S R 3 E S 2 B T.

A Fir, 32 ins. in diam., bears N.10\*W., 31 lks. dist., marked T 29 S R 3 E S 35 B T.

Land, mountainous.

Soil, rocky, 2nd rate.

Timber, fir and pine.

Undergrowth, buck brush, manzanita, small fir and pine.

West, bet secs. 2 and 35.

Over mountainous land, through medium timber and dense undergrowth.