

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 3 E.

CHAINS
 12.20 Desc. 55 ft. over SW. slope.
 40.00 Creek, 4 lks. wide, course SE., asc. 320 ft. over E. slope to
 80.00 Set an iron post, 3 ft. long, 1 in. in diam., 22 ins. in the ground, to a rock too large to be moved, and build a mound of stone, 2 ft. base. 1 ft. high, around the post, for $\frac{1}{4}$ sec. cor. with brass cap marked

$$\begin{array}{r} \frac{1}{4} \text{ S } 35 \\ \frac{1}{4} \text{ S } 2 \\ \hline 1927 \end{array}$$

From which

- A Fir, 10 ins. in diam., bears N.24*W., 27 lks. dist. marked $\frac{1}{4}$ S 35 B T.
- A Fir, 6 ins. in diam., bears S.20*E., 8 lks. dist. marked $\frac{1}{4}$ S 2 B T.

Asc. 390 ft. over general E. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 2, 3, 34 & 35, with brass cap marked

$$\begin{array}{r} \text{T 29 S R 3 E} \\ \text{S 34 | S 35} \\ \text{S 3 | S 2} \\ \hline \text{T 30 S} \\ 1927 \end{array}$$

From which

- A Fir, 14 ins. in diam., bears N.31*E., 41 lks. dist., marked T 29 S R 3 E S 35 B T.
- A Fir, 10 ins. in diam., bears S.65 $\frac{1}{2}$ *E., 161 lks. dist., marked T 30 S R 3 E S 2 B T.
- A Fir, 24 ins. in diam., bears S.69*W., 104 lks. dist. marked T 30 S R 3 E S 3 B T.
- A Fir, 28 ins. in diam., bears N.5*W., 22 lks. dist., marked T 29 S R 3 E S 34 B T.

Land: Rolling mountainous.
 Soil: Sandy loam & rocky. 2nd rate.
 Timber: Fir, pine & cedar.
 Undergrowth: Huckleberry, yew, Vine maple, small fir & pine.