

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S.R. 3 E.

CHAINS

West bet. secs. 3 & 34.

Over mountainous land, through medium timber and medium undergrowth.

Asc. 245 ft. over E. slope.

3.85 Forest Service Trail, bears NE. & SW.

12.50 Spur, slopes SE., desc. 70 ft. over SW. slope.

22.00 Draw, drains S., asc. 70 ft. over SE. slope to

31.20 Creek, 5 lks. wide, course SE., asc. 210 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap marked

1/4 S 34
S 3
1927

From which

A Hemlock, 6 ins. in diam., bears N.9*W., 15 lks. dist. dist., marked 1/4 S 34 B T.

A Fir, 24 ins. in diam., bears S.36*E., 44 lks. dist. marked 1/4 S 3 B T.

Asc. 300 ft. over E. slope.

45.60 Forest Service Telephone line, bears N. & S.

56.10 Ridge, bears N. & S., desc. 590 ft. over SW. slope.

77.00 Draw, drains SW., asc. 20 ft. over SE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 3,4,33 & 34, with brass cap marked

T 29 S R 3 E
S 33 | S 34
S 4 | S 3
T 30 S
1927

From which

A Fir, 28 ins. in diam., bears N.21*E., 52 lks. dist., marked T 29 S.R 3 E S 34 B T.

A Fir, 26 ins. in diam., bears S.84*E., 105 lks. dist., marked T 30 S R 3 E S 3 B T.